



Prepared according to 29CFR 1910.1200.

1	<b>Chemical Product and Company Identification</b>
---	--

***CPI FLUID ENGINEERING  
A DIV. OF THE LUBRIZOL CORPORATION  
2300 JAMES SAVAGE ROAD  
MIDLAND, MI 48642  
989-496-3780***

<b>Product Trade Name</b>	QUINSYN-NG-68
<b>CAS Number</b>	Not applicable for mixtures.
<b>Synonyms</b>	None.
<b>Generic Chemical Name</b>	Mixture.
<b>Product Type</b>	Multipurpose.
<b>Preparation/Revision Date</b>	23 August 2013
<b>Transportation Emergency Phone No.</b>	FOR TRANSPORT EMERGENCY call CHEMTREC: (+1) 703-527-3887 (outside the U.S.), 1-800-424-9300 (in the U.S.)
<b>MSDS No.</b>	13462354-1429148-402371-102103

2	<b>Hazards Identification</b>
---	-------------------------------

<b>Appearance</b>	Clear to yellow liquid.
<b>Odor</b>	Mild
<b>Principal Hazards</b>	<ul style="list-style-type: none"> <li>This material has no known health hazards.</li> </ul>

See Section 11 for complete health hazard information.

3	<b>Composition/Information on Ingredients</b>
---	---

<b>Hazardous Ingredients</b>	This material has no known hazards under applicable laws.
------------------------------	---

4	<b>First Aid Measures</b>
---	---------------------------

<b>Eyes</b>	Flush with water at least 30 minutes. Get medical attention if eye irritation develops or persists.
<b>Skin</b>	Wash with soap and water. Remove contaminated clothing. Get medical attention if irritation develops. Launder contaminated clothing before reuse.
<b>Inhalation</b>	Remove exposed person to fresh air if adverse effects are observed. If breathing is labored, administer oxygen. If breathing has stopped, apply artificial respiration. If experiencing respiratory symptoms call a poison center or doctor.
<b>Oral</b>	Do NOT induce vomiting. Never give anything by mouth to a person who is losing consciousness, unconscious or convulsing. Call a poison center or doctor if exposed or you feel unwell.
<b>Additional Information</b>	Note to physician: Treat symptomatically.

5	<b>Fire Fighting Measures</b>
---	-------------------------------

<b>Flash Point</b>	>= 226 °C, 440.1 °F ASTM D 92 (Minimum)
<b>Extinguishing Media</b>	CO <sub>2</sub> , dry chemical, foam, water spray, water fog. Water can be used to cool and protect exposed material.
<b>Firefighting Procedures</b>	Recommend wearing self-contained breathing apparatus. Do not direct a solid stream of water on spilled material. Use flooding amounts of water as a fog. Use water to cool containers exposed to fire. A solid stream of water will spread the burning material. Material creates a special hazard because it floats on water. Do not release chemically contaminated water

into drains, soil or surface water.

**Unusual Fire & Explosion Hazards** Burning may produce irritating, toxic and obnoxious fumes. Container may rupture in a fire situation. DO NOT USE a solid stream of water. See section 10 for additional information.

<b>6</b>	<b>Accidental Release Measures</b>
----------	------------------------------------

**Spill Procedures** Only trained personnel should be permitted in area. Personal Protective Equipment must be worn, see Personal Protection Section for PPE recommendations. Ventilate area if spilled in confined space or other poorly ventilated areas. Shut off leak if without risk. Prevent entry into sewers and waterways. Material on floors may be slippery. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Place in metal containers for recovery or disposal. Pump any free liquid into an appropriate closed container.

<b>7</b>	<b>Handling and Storage</b>
----------	-----------------------------

**Pumping Temperature** Not determined.

**Maximum Handling Temperature** Not determined.

**Handling Procedures** Keep containers closed when not in use. Avoid eye contact. Avoid repeated or prolonged skin contact. When handling, do not eat, drink, or smoke. Product can accumulate static charge when handled. Equipment should be grounded. Use grounding and bonding connection when transferring material to prevent static discharge, fire and explosion. Use spark-resistant tools. Wash thoroughly after handling. Launder contaminated clothing before reuse. Empty containers retain material residue. Do not cut, weld, braze, solder, drill, grind or expose containers to heat, flame, spark or other sources of ignition. Dispose of packaging or containers in accordance with local, regional, national and international regulations.

**Maximum Storage Temperature** Not determined.

**Storage Procedures** Store separately from oxidizers. Store in a cool, dry, well-ventilated area. Store separately from incompatible materials. Keep container tightly closed. Do not store in open, unlabeled or mislabeled containers. See section 10 for incompatible materials.

**Maximum Loading Temperature** Not determined.

<b>8</b>	<b>Exposure Controls/Personal Protection</b>
----------	--

**Exposure Limits** None established

**Other Exposure Limits** Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH TWA of 5 mg per cubic meter.

**Engineering Controls** If use generates a mist or vapor, local exhaust ventilation is recommended. Additional ventilation or exhaust may be required to maintain air concentrations below recommended exposure limits.

**Gloves Procedures** Nitrile. Consult clothing/glove manufacturer to determine appropriate type of glove for given situation. Gloves should always be inspected before each use and discarded if they show tears, pinholes, or signs of wear. Use good industrial hygiene practices to avoid skin contact. If contact with the material may occur wear chemically protective gloves.

**Eye Protection** Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

**Respiratory Protection** Use NIOSH/MSHA approved respirator with a combination organic vapor and high efficiency filter cartridge if recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

**Clothing Recommendation** Long sleeve shirt is recommended. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction. Launder contaminated clothing before reuse.

<b>9</b>	<b>Physical and Chemical Properties</b>
----------	---

**Flash Point**  $\geq 226$  °C, 440.1 °F ASTM D 92 (Minimum)

**Upper Flammable Limit** Not determined.

**Lower Flammable Limit** Not determined.

**Autoignition Point** Not determined.

**Explosion Data** Material does not have explosive properties.

**Vapor Pressure** Not determined.

**pH** Not determined.

**Specific Gravity** 0.87 (20 °C)

**Bulk Density** 7.24 Lb/gal, 0.87 Kg/L

**Water Solubility** Insoluble.

**Percent Solid** Not determined.

**Percent Volatile** Not determined.

**Volatile Organic Compound** Not determined.

**Vapor Density** Not determined.

**Evaporation Rate** Not determined.

**Odor** Mild

**Appearance** Clear to yellow liquid.

<b>Viscosity</b>	69 Centistokes (40 °C) 9.1 Centistokes (100 °C)
<b>Odor Threshold</b>	Not determined.
<b>Boiling Point</b>	Not determined.
<b>Pour Point Temperature</b>	Not determined.
<b>Melting / Freezing Point</b>	Not determined.

*The above data are typical values and do not constitute a specification. Vapor pressure data are calculated unless otherwise noted.*

<b>10</b>	<b>Stability and Reactivity</b>
-----------	---------------------------------

<b>Stability</b>	Material is normally stable at moderately elevated temperatures and pressures.
<b>Decomposition Temperature</b>	Not determined.
<b>Incompatibility</b>	Oxidizing agents.
<b>Polymerization</b>	Will not occur.
<b>Thermal Decomposition</b>	Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion.
<b>Conditions to Avoid</b>	Do not expose to excessive heat, ignition sources, or oxidizing materials.

<b>11</b>	<b>Toxicological Information</b>
-----------	----------------------------------

**-- ACUTE EXPOSURE --**

<b>Eye Irritation</b>	Not expected to cause eye irritation. Based on data from components or similar materials.
<b>Skin Irritation</b>	Not expected to be a primary skin irritant. Based on data from components or similar materials. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, and cracking of the skin.
<b>Respiratory Irritation</b>	If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. Based on data from components or similar materials.
<b>Dermal Toxicity</b>	The LD50 in rabbits is > 2000 mg/Kg. Based on data from components or similar materials.
<b>Inhalation Toxicity</b>	No data available to indicate product or components may be a toxic inhalation hazard.
<b>Oral Toxicity</b>	The LD50 in rats is > 10,000 mg/Kg. Based on data from components or similar materials.
<b>Dermal Sensitization</b>	No data available to indicate product or components may be a skin sensitizer.
<b>Inhalation Sensitization</b>	No data available to indicate product or components may be respiratory sensitizers.

**-- CHRONIC EXPOSURE --**

<b>Chronic Toxicity</b>	No data available to indicate product or components present at greater than 1% are chronic health hazards.
<b>Carcinogenicity</b>	This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Reproductive Toxicity</b>	No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.
<b>Teratogenicity</b>	No data available to indicate product or any components contained at greater than 0.1% may cause birth defects.

**-- ADDITIONAL INFORMATION --**

<b>Other</b>	No other health hazards known.
--------------	--------------------------------

<b>12</b>	<b>Ecological Information</b>
-----------	-------------------------------

**-- ENVIRONMENTAL TOXICITY --**

<b>Freshwater Fish Toxicity</b>	The acute LC50 is 100 - 1000 mg/L based on component data.
<b>Freshwater Invertebrates Toxicity</b>	Not determined.
<b>Algal Inhibition</b>	Not determined.
<b>Saltwater Fish Toxicity</b>	Not determined.
<b>Saltwater Invertebrates Toxicity</b>	Not determined.
<b>Bacteria Toxicity</b>	The acute EC50 is 100 - 1000 ppm based on component data.
<b>Miscellaneous Toxicity</b>	Not determined.

**-- ENVIRONMENTAL FATE --**

<b>Biodegradation</b>	At least 25% of the components in this product show moderate biodegradation based on OECD 301-type test data. At least 25% of the components in this product show moderate biodegradation based on OECD 302-type test data.
<b>Bioaccumulation</b>	Less than 1.0% of the components potentially bioconcentrate, based on octanol/water coefficients.

**Soil Mobility** Not determined.

<b>13</b>	<b>Disposal Considerations</b>
-----------	--------------------------------

**Waste Disposal** This material, if discarded, is not a hazardous waste under RCRA Regulation 40 CFR 261. Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

<b>14</b>	<b>Transport Information</b>
-----------	------------------------------

<b>ICAO/IATA I</b>	Not regulated.
<b>ICAO/IATA II</b>	Not regulated.
<b>IMDG</b>	Not regulated.
<b>IMDG EMS Fire</b>	Not applicable.
<b>IMDG EMS Spill</b>	Not applicable.
<b>IMDG MFAG</b>	Not applicable.
<b>MARPOL Annex II</b>	Not determined.
<b>USCG Compatibility</b>	Not determined.
<b>U.S. DOT Bulk</b>	Not regulated.
<b>DOT NAERG</b>	Not applicable.
<b>U.S. DOT (Intermediate)</b>	Not regulated.
<b>U.S. DOT Intermediate NAERG</b>	Not applicable.
<b>U.S. DOT Non-Bulk</b>	Not regulated.
<b>U.S. DOT Non-Bulk NAERG</b>	Not applicable.
<b>Canada</b>	Not regulated.
<b>Mexico</b>	Not regulated.
<b>Bulk Quantity</b>	85000 KG, 187391 lbs.
<b>Intermediate Quantity</b>	11000 KG, 24251 lbs.
<b>Non-Bulk Quantity</b>	400 KG, 882 lbs.

*Review classification requirements before shipping materials at elevated temperatures.*

<b>15</b>	<b>Regulatory Information</b>
-----------	-------------------------------

**-- Global Chemical Inventories --**

<b>USA</b>	All components of this material are on the US TSCA Inventory or are exempt.
<b>Other TSCA Reg.</b>	None known.
<b>EU</b>	To obtain information on the REACH compliance status of this product, please visit <a href="http://Lubrizol.com/REACH">Lubrizol.com/REACH</a> , or e-mail us at <a href="mailto:REACH_MSDS_INQUIRIES@Lubrizol.com">REACH_MSDS_INQUIRIES@Lubrizol.com</a>
<b>Japan</b>	All components are in compliance with the Chemical Substances Control Law of Japan.
<b>Australia</b>	All components are in compliance with chemical notification requirements in Australia.
<b>New Zealand</b>	All components are in compliance with chemical notification requirements in New Zealand.
<b>Canada</b>	All components are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List.
<b>Switzerland</b>	All components are in compliance with the Environmentally Hazardous Substances Ordinance in Switzerland.
<b>Korea</b>	All components are in compliance in Korea.
<b>Philippines</b>	All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).
<b>China</b>	All components of this product are listed on the Inventory of Existing Chemical Substances in China.
<b>Taiwan</b>	May require notification before sale in Taiwan.

**-- Other U.S. Federal Regulations --**

<b>SARA Ext. Haz. Subst.</b>	This product does not contain greater than 1.0% of any chemical substance on the SARA Extremely Hazardous Substances list.
<b>SARA Section 313</b>	This product does not contain greater than 1.0% (greater than 0.1% for carcinogenic substance) of any chemical substances listed under SARA Section 313.

<b>SARA 311 Classifications</b>	Acute Hazard	No
	Chronic Hazard	No
	Fire Hazard	No
	Reactivity Hazard	No

**CERCLA Hazardous Substances** None known.

-- State Regulations --

**Cal. Prop. 65**

This product contains the following chemical(s) known to the state of California to cause cancer and/or birth defects based on maximum impurity levels of components: 8 ppm Ethyl acrylate, CAS no. 140-88-5

-- Product Registrations --

**U.S. Fuel Registration** Not applicable.  
**Finnish Registration Number** Not Registered  
**Swedish Registration Number** Not Registered  
**Norwegian Registration Number** Not Registered  
**Danish Registration Number** Not Registered  
**Swiss Registration Number** Not Registered  
**Italian Registration Number** Not Registered

-- Other / International --

**Miscellaneous Regulatory Information** Not determined.

<b>16</b>	<b>Other Information</b>
-----------	--------------------------

**US NFPA Codes**

Health	Fire	Reactivity	Special
1	1	0	N/E

(N/E) - None established

**HMIS Codes**

Health	Fire	Reactivity
0	1	0

**Precautionary Labels**

- This material has no known health hazards.

**Revision Indicators**

Section: 8 Glove protection.  
 Section: 12 Bioconcentration

Changed: 19 July 2013  
 Changed: 23 August 2013

*As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.*