1	Manufacture	MODE	Quinay Com-			
			Quincy Compressor			
	Model Number: QGDV 20			Date:	Feb	-18
2	X Air-cooled Water-cooled			Type:	Screw	
	X Oil-injected Oil-free			# of Stages:	Single	
3	Rated Opera	ting Press	sure	100	psig ^b	
4	Drive Motor Nominal Rating			20	hp	
5	Drive Motor Nominal Efficiency			91	percent	
6	Fan Motor Nominal Rating (if applicable)			1	hp	
7	Fan Motor Nominal Efficiency			65	percent	
	Input Power (kW)			Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d	
-	20.3 Max			102.6	19.8	
Or!	17.7			90.7	19.5	
8*	13.4			66.7	20.1	
	11.3			55.1	20.5	
	8.7			38.8	22.4	
	7.7 Min			33.5	23.0	
9*	Total Packag	e Input P	Power at Zero Flow ^{c, d}	0.0	kW	
10	Specific Power (kW/100 A.CFM)	30.0 25.0 20.0				
		15.0				
		10.0	25.0 50.0	75.0 100	0.0 125.0	
		0.0	Note: Graph is only a visual r Note: Y-Axis Scale, 10 to 35, + 5kV	75.0 100 city (ACFM) representation of the data in Secti V/100acfm increments if necessary a 55% over maximum capacity	on 8	
Consult C. NOTES: Member	AGI website for a a. Measured ISO 1217. b. The opera c. No Load I manufactu d. Tolerance	0.0 n the CAG list of part at the disch the disch the perssur Power. In au irer may sta is specified he terms "per Volu	Capa Note: Graph is only a visual r Note: Y-Axis Scale, 10 to 35, + 5kV X-Axis Scale, 0 to 2 I Performance Verification I icipants in the third party ve targe terminal point of the com the actual cubic feet per mi e at which the Capacity and El ccordance with ISO 1217, Anne te "not significant" or "0" on th i in ISO 1217, Annex E, as sho ower" and "energy" are synony me Flow Rate	city (ACFM) representation of the data in Sectiv V/100acfm increments if necessary a 55% over maximum capacity Program, these items are ve erification program: <u>y</u> pressor package in accordance nute at inlet conditions. lectrical Consumption were m tex E, if measurement of no lo he test report. wh in table below: mous for purposes of this doc	rified by program admin www.cagi.org e with easured for this data sheet ad power equals less than ument. Specific Energy	1%, No Load / Zero Flov
Consult CA NOTES:	AGI website for a a. Measured ISO 1217. b. The opera c. No Load I manufactt d. Tolerance NOTE: T	0.0 n the CAG list of part at the disch , Annex E; a iting pressur Power. In au irer may sta is specified the terms "pu Volu at spec	Capa Note: Graph is only a visual r Note: Y-Axis Scale, 10 to 35, + 5kV X-Axis Scale, 0 to 2 I Performance Verification I icipants in the third party ve arge terminal point of the com acfm is actual cubic feet per mi e at which the Capacity and El ccordance with ISO 1217, Ann te "not significant" or "0" on tl in ISO 1217, Annex E, as sho ower" and "energy" are synony me Flow Rate ified conditions	city (ACFM) representation of the data in Section W/100acfm increments if necessary a 55% over maximum capacity Program, these items are ve erification program: pressor package in accordance nute at inlet conditions. lectrical Consumption were m tex E, if measurement of no lo he test report. wur in table below:	n 8 above 35 rified by program admin www.cagi.org e with easured for this data sheet ad power equals less than ument.	
Consult C. NOTES: Member	AGI website for a a. Measured ISO 1217, b. The opera c. No Load I manufactu d. Tolerance NOTE: T	0.0 n the CAG list of part at the disch the disch the perssur Power. In au irer may sta is specified he terms "per Volu	Capa Note: Graph is only a visual r Note: Y-Axis Scale, 10 to 35, + 5kV X-Axis Scale, 0 to 2 I Performance Verification I icipants in the third party ve targe terminal point of the com the actual cubic feet per mi e at which the Capacity and El ccordance with ISO 1217, Anne te "not significant" or "0" on th i in ISO 1217, Annex E, as sho ower" and "energy" are synony me Flow Rate	city (ACFM) representation of the data in Sectiv V/100acfm increments if necessary a 55% over maximum capacity Program, these items are ve erification program:y pressor package in accordance nute at inlet conditions. lectrical Consumption were m tex E, if measurement of no lo he test report. wn in table below: mous for purposes of this doc Volume Flow Rate	n 8 above 35 rified by program admin www.cagi.org e with easured for this data sheet ad power equals less than ument. Specific Energy Consumption	1%, No Load / Zero Flow
Consult C. NOTES: Member	AGI website for a a. Measured ISO 1217, b. The opera c. No Load I manufactu d. Tolerance NOTE: T <u>massissi massissi massissi Belevices</u>	0.0 n the CAG list of part at the disch Annex E; a ting pressur Power. In ad rer may sta is specified he terms "po Volu at spec /min	Capa Note: Graph is only a visual r Note: Y-Axis Scale, 10 to 35, + 5kV X-Axis Scale, 0 to 2 I Performance Verification I icipants in the third party ve arge terminal point of the com acfm is actual cubic feet per mi te at which the Capacity and El ccordance with ISO 1217, Anne te "not significant" or "0" on th in ISO 1217, Annex E, as sho ower" and "energy" are synony me Flow Rate ified conditions <u>ft3 / min</u>	city (ACFM) representation of the data in Section W100acfm increments if necessary as solved as a sector of the se	n 8 above 35 rified by program admin <u>www.cagi.org</u> e with easured for this data sheet ad power equals less than <u>ument.</u> Specific Energy <u>Consumption</u> %	1%, No Load / Zero Flow