		COMPRESSOR DATA SHEET Rotary Compressor: Variable Speec	j Date:	November 9, 2018
A	Manufacturer:	Quincy Compressor		
В	Base Model:	QGDV-25		
С	Cooling:	Air-Cooled		
D	Туре:	Oil-Injected Screw		
E	Stages:	1		
F	Drive Motor Nominal	Rating	25	hp
n	Full-load package Isen at Rated Capacity and	tropic Efficiency Full Load Operating Pressure ^e	67.0	Percent ^e
G	Rated Capacity at Full Load Operating Pressure ^a		127.1	acfm ^a
н	Full Load Operating Pressure ^b		100	psig ^b
I	Maximum Full Flow Operating Pressure		150	psig ^c
J	Pressure Ratio ^f		7.9	
ĸ	Total Package Input Po Operating Pressure ^d	ower at Rated Capacity and Full Load	25.3	kW ^d
	Specific Package Input Operating Pressure	Power at Rated Capacity and Full Load	19.90	kW/100 cfm
		ls according to the U.S. Department of Energy (DOE) Ene the Federal Register for additional information		itandards for Air Compresso ederalregister.gov
NOTES: Member	ACFM is actual cu	discharge terminal point of the compressor package in a bic feet per minute at inlet conditions. ssure at which the Capacity (Item G) and Electrical Const t.		



- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins.
- d. Total package input power at other than reported operating points will vary with control strategy.

e. Isentropic Efficiency = theoretical power required divided by real measurement performance at same flow and pressure **For Variable Speed, this value combines 3 Measured Points: (25% x 40%LOAD) + (50% x 70%LOAD) + (25% x 100%LOAD)

f. Pressure Ratio = the ratio of discharge pressure to inlet pressure, as determined at full-load operating pressure For more information go to: https://www.quincycompressor.com/resources/data-sheets/

This form was developed by Quincy Compressor to publish equipment performance data in accordance with applicable energy conservation standards adopted under EPCA (42 U.S.C. 6295(s) and 6316(a))