COMPTON OF		COMPRESSOR DATA SHEET Rotary Compressor: Variable Speed	d Date:	November 9, 2018
A	Manufacturer:	Quincy Compressor		
В	Base Model:	QGDV-30		
С	Cooling:	Air-Cooled		
D	Туре:	Oil-Injected Screw		
E	Stages:	1		
F	Drive Motor Nomina	Il Rating	30	hp
$\eta_{isen}$	Full-load package lse at Rated Capacity an	entropic Efficiency d Full Load Operating Pressure <sup>e</sup>	68.3	Percent <sup>e</sup>
G	Rated Capacity at Fu	ll Load Operating Pressure <sup>a</sup>	141.3	acfm <sup>a</sup>
н	Full Load Operating Pressure <sup>b</sup>		125	psig <sup>b</sup>
I	Maximum Full Flow Operating Pressure		150	psig <sup>c</sup>
J	Pressure Ratio <sup>f</sup>		9.6	
К	Total Package Input Operating Pressure <sup>d</sup>	Power at Rated Capacity and Full Load	30.7	kW <sup>d</sup>
	Specific Package Inp Operating Pressure	ut Power at Rated Capacity and Full Load	21.72	kW/100 cfm
		dels according to the U.S. Department of Energy (DOE) Ene in the Federal Register for additional information		Standards for Air Compress federalregister.gov
NOTES: Member	ACFM is actual b. The operating p for this data sh	e discharge terminal point of the compressor package in a cubic feet per minute at inlet conditions. oressure at which the Capacity (Item G) and Electrical Cons eet. sure attainable at full flow, usually the unload pressure set	sumption (Item K)	were measured



- maximum pressure attainable before capacity control begins.
- d. Total package input power at other than reported operating points will vary with control strategy.

e. Isentropic Efficiency = theoretical power required divided by real measurement performance at same flow and pressure \*\*For Variable Speed, this value combines 3 Measured Points: (25% x 40%LOAD) + (50% x 70%LOAD) + (25% x 100%LOAD)

f. Pressure Ratio = the ratio of discharge pressure to inlet pressure, as determined at full-load operating pressure For more information go to: https://www.quincycompressor.com/resources/data-sheets/

\*\*\*This form was developed by Quincy Compressor to publish equipment performance data in accordance with applicable energy conservation standards adopted under EPCA (42 U.S.C. 6295(s) and 6316(a))\*\*\*