

COMPRESSOR DATA SHEET

Rotary Compressor: Variable Speed



Date: November 9, 2018

А	Manufacturer:	Quincy Compressor		
В	Base Model:	QGDV-30		
С	Cooling:	Air-Cooled		
D	Type:	Oil-Injected Screw		
E	Stages:	1		
F	Drive Motor Nominal Rating		30	hp
η_{isen}	Full-load package Isentropic Efficiency at Rated Capacity and Full Load Operating Pressure e		68.2	Percent ^e
G	Rated Capacity at Full Load Operating Pressure ^a		154.5	acfm ^a
Н	Full Load Operating Pressure b		100	psig ^b
I	Maximum Full Flow Operating Pressure ^c		150	psig ^c
J	Pressure Ratio ^f		7.9	
K	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		31.0	kW^d

^{*} Quincy Compressors tests all models according to the U.S. Department of Energy (DOE) Energy Conservation Standards for Air Compressors.

Consult the Final Rule (82 FR 1052) in the Federal Register for additional information

https://www.federalregister.gov

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item G) and Electrical Consumption (Item K) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins.
- ${\bf d.}\ \ {\bf Total}\ package\ input\ power\ at\ other\ than\ reported\ operating\ points\ will\ vary\ with\ control\ strategy.$
- e. Isentropic Efficiency = theoretical power required divided by real measurement performance at same flow and pressure

 **For Variable Speed, this value combines 3 Measured Points: (25% x 40%LOAD) + (50% x 70%LOAD) + (25% x 100%LOAD)
- f. Pressure Ratio = the ratio of discharge pressure to inlet pressure, as determined at full-load operating pressure For more information go to: https://www.quincycompressor.com/resources/data-sheets/



^{***}This form was developed by Quincy Compressor to publish equipment performance data in accordance with applicable energy conservation standards adopted under EPCA (42 U.S.C. 6295(s) and 6316(a))***