COMPRESSOR DATA SHEET

Rotary Screw Compressor

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: **Quincy Compressor**		
2	Model Number: **QSI-440i** [X] Air-cooled [ ] Water-cooled [X] Oil-injected [ ] Oil-free	# of Stages:	Date: **May 2011** **Single**
3*	Rated Capacity at Full Load Operating Pressure [a, f]	**436**	acfm [a,f]
4	Full Load Operating Pressure [b]	**125**	psig [b]
5	Maximum Full Flow Operating Pressure [c]	**140**	psig [c]
6	Drive Motor Nameplate Rating	**100**	hp
7	Drive Motor Nameplate Nominal Efficiency	**94.1**	percent
8	Fan Motor Nameplate Rating (if applicable)	**3**	hp
9	Fan Motor Nameplate Nominal Efficiency	**81.5**	percent
10*	Total Package Input Power at Zero Flow [e]	**27.1**	kW [e]
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure [d]	**90.4**	kW [d]
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure [g]	**20.7**	kW/100 cfm [g]

*** For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party program administrator**

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
d. Total package input power at other than reported operating points will vary with control strategy.
e, f, g. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

Member:

Volume Flow Rate at specified conditions		Volume Flow Rate [f]	Specific Energy [g] Consumption	No Load / Zero Flow Power [e]
m^3 / min	ft3 / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	
0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10%
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	