

HI781C-0 - Marine Nitrate Low Range Reagent C

Dated 4/6/2023 Printed on 4/6/2023 Page n. 1 / 10 Replaced revision:2 (Dated 11/17/202

# Safety Data Sheet

According to U.S.A. Federal Hazcom 2012 and Canadian HPR - WHMIS 2015

## 1. Identification

1.1. Product identifier

Code HI781C-0

Product name Marine Nitrate Low Range Reagent C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Determination of Nitrate in Seawater Samples.

1.3. Details of the supplier of the safety data sheet

Name Hanna Instruments S.R.L.

Full address str. Hanna Nr 1

District and Country 457260 loc. Nusfalau (Salaj)

Romania
Tel. +40 260607700
Fax +40 260607700

e-mail address of the competent person

responsible for the Safety Data Sheet msds@hanna.ro

Supplier: Hanna Instruments, Inc - 584 Park East Drive, Woonsocket, Rhode Island, USA

02895 - Technical Service Contact Information: +1 8004266287 - e-mail:

sds@hannainst.com

1.4. Emergency telephone number

For urgent inquiries refer to USA Emergency Contact Information: +1 8004249300 - CHEMTREC 24 hours/365

days - International Emergency Contact Information: +1 7035273887 - CHEMTREC

24 hours/365 days

#### 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Acute toxicity, category 3
Skin corrosion, category 1

Serious eye damage, category 1

Hazard pictograms:

Toxic if inhaled.

Causes severe skin burns and eye damage.

Causes serious eye damage.





Signal words: Danger

Hazard statements:

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

Precautionary statements:

Prevention:

P260 Do not breathe dust, fume, gas, mist, vapours, spray.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

Response:

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to



HI781C-0 - Marine Nitrate Low Range Reagent C

Immediately call a POISON CENTER or doctor.

Revision nr.3 Dated 4/6/2023 Printed on 4/6/2023 Page n. 2 / 10 Paglaced revision: 2 (Dated 11/17/2023 ΕN

2. Hazards identification

... 1 ---

do. Continue rinsing.

P310

Storage:

\_\_

Disposal:

\_\_

2.2. Other hazards

Additional hazards

Corrosive to the respiratory tract.

#### 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification:

POTASSIUM DISULFATE

50 ≤ x < 100 Acute toxicity, category 3 H331, Skin corrosion, category 1A H314, Serious

eye damage, category 1 H318

EC 232-216-8 CAS 7790-62-7

REACH Reg. 01-2119987095-26

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### 4. First-aid measures

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

## POTASSIUM DISULFATE

Irritation and corrosion, Cough, Shortness of breath. Risk of blindness!.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

#### 5. Fire-fighting measures

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

<sup>\*</sup> There is a batch to batch variation.

## HI781C-0 - Marine Nitrate Low Range Reagent C

Dated 4/6/2023 Printed on 4/6/2023 Page n. 3 / 10 Replaced revision: 2 (Dated 11/17/202)

## 5. Fire-fighting measures

POTASSIUM DISUI FATE

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Sulphur oxides.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

#### 7. Handling and storage

## 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

## 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

## 7.3. Specific end use(s)

Information not available

## 8. Exposure controls/personal protection

#### 8.1. Control parameters

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (OSHA 29 CFR 1910.138).

## HI781C-0 - Marine Nitrate Low Range Reagent C

Dated 4/6/2023 Printed on 4/6/2023 Page n. 4 / 10 Replaced revision:2 (Dated 11/17/2022)

## 8. Exposure controls/personal protection

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

Use a NIOSH certified filtering facemask (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134) or equivalent device, whose class and effective need, must be defined according to the outcome of risk assessment.

**ENVIRONMENTAL EXPOSURE CONTROLS** 

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties Value
Appearance powder
Colour white
Odour odourless
Odour threshold not available

pH 1

Method:ASTM D1293-18 Concentration: 1.5 % Temperature: 25 °C

Information

Melting point / freezing point not available Initial boiling point not applicable Boiling range not available not applicable Flash point Evaporation rate not available Flammability not available Lower inflammability limit not available Upper inflammability limit not available Lower explosive limit not available Upper explosive limit not available Vapour pressure not available not available Vapour density 1.05

Relative density

Relative density

Solubility

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

Explosive properties

Oxidising properties

not available
not available
not applicable
not applicable

9.2. Other information

Total solids (250°C / 482°F) 100,00 %

## 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

### 10.4. Conditions to avoid

Avoid environmental dust build-up.

#### POTASSIUM DISULFATE

Exposure to moisture.

EPY 11.3.0 - SDS 1004.14



## HI781C-0 - Marine Nitrate Low Range Reagent C

Dated 4/6/2023 Printed on 4/6/2023 Page n. 5 / 10 Replaced revision:2 (Dated 11/17/2022)

10. Stability and reactivity

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

## 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

#### POTASSIUM DISULFATE

Acute inhalation toxicity, absorption, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages, damage of respiratory tract, Lung oedema, Symptoms may be delayed - Skin irritation (in analogy to similar products), Causes severe burns. - Eye irritation (in analogy to similar products), Causes serious eye damage. Risk of blindness!

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Corrosive to the respiratory tract.

POTASSIUM DISULFATE

LD50 (Oral): LC50 (Inhalation mists/powders): 2140 mg/kg Rat 0.85 mg/l/4h Rat

## SKIN CORROSION / IRRITATION

Corrosive for the skin

Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

# HI781C-0 - Marine Nitrate Low Range Reagent C

Dated 4/6/2023 Printed on 4/6/2023 Page n. 6 / 10 Replaced revision: 2 (Dated 11/17/2022)

11. Toxicological information

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

POTASSIUM DISULFATE

LC50 - for Fish 680 mg/l/96h Pimephales promelas

EC50 - for Crustacea 720 mg/l/48h Daphnia magna

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Other adverse effects

Information not available

#### 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

#### 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 2923

14.2. UN proper shipping name

ADR / RID: CORROSIVE SOLID, TOXIC, N.O.S. (Potassium Disulfate mixture) IMDG: CORROSIVE SOLID, TOXIC, N.O.S. (Potassium Disulfate mixture) IATA: CORROSIVE SOLID, TOXIC, N.O.S. (Potassium Disulfate mixture)

# HI781C-0 - Marine Nitrate Low Range Reagent C

Revision nr.3 Dated 4/6/2023 Printed on 4/6/2023 Page n. 7 / 10 Penlaced revision: 2 (Dated 11/17/2022) ΕN

14. Transport information

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8 (6.1)

IMDG: Class: 8 Label: 8 (6.1)

IATA: Class: 8 Label: 8 (6.1)



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 86 Limited Quantities: 1 kg Tunnel restriction code: (E)

Special provision: -

IMDG: EMS: F-A, S-B Limited Quantities: 1 kg IATA: Cargo: Maximum quantity: 50 Kg

ATA: Cargo: Maximum quantity: 50 Kg Packaging instructions: 863
Pass.: Maximum quantity: 15 Kg Packaging instructions: 859

Special provision: A3, A803

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

# 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### U.S. Federal Regulations

#### TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

@EPY 11.3.0 - SDS 1004.14

#### EN



# Hanna Instruments S.R.L.

## HI781C-0 - Marine Nitrate Low Range Reagent C

Revision nr.3 Dated 4/6/2023 Printed on 4/6/2023 Page n. 8 / 10 Replaced revision:2 (Dated 11/17/2022)

15. Regulatory information

No component(s) listed.

EPA List of Lists:
313 Category Code:
No component(s) listed.

EPCRA 302 EHS TPQ: No component(s) listed.

EPCRA 304 EHS RQ: No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ: No component(s) listed.

State Regulations

Massachussetts:

No component(s) listed.

Minnesota:

No component(s) listed.

New Jersey:

No component(s) listed.

New York:

No component(s) listed.

Pennsylvania:

No component(s) listed.

California:

No component(s) listed.

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

## 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

#### LEGEND

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)

## HI781C-0 - Marine Nitrate Low Range Reagent C

Dated 4/6/2023 Printed on 4/6/2023 Page n. 9 / 10 Replaced revision: 2 (Dated 11/17/2022

#### 16. Other information

- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

#### GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.





HI781C-0 - Marine Nitrate Low Range Reagent C

Revision nr.3 Dated 4/6/2023 Printed on 4/6/2023 Page n. 10 / 10 Replaced revision:2 (Dated 11/17/2022)

16. Other information ... / >>

Changes to previous review: The following sections were modified: 09 / 11.

EPY 11.3.0 - SDS 1004.14