



# Performance Plus Greases

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

## CONSTRUCTION RED GREASE

**PERFORMANCE PLUS Construction Red Grease** is engineered for extended use in many agricultural, construction, and industrial applications and provides a tenacious lubricating film for moving parts.

Construction Red Grease meets the ever-increasing equipment requirements for film strength, operating temperatures, stability, and lubricant life. Additionally, Construction Red provides superior protection against spalling and wear as well as excellent protection against rust and corrosion.

**PREMIUM BASE OILS:** We begin with quality base stocks that provide excellent oxidative stability, and high VI to maintain film thickness over a wide range of temperatures

**LITHIUM COMPLEX THICKENER:** Our lithium complex provides a high temperature operating range with a dropping point of 500°F

**FORTIFIED WITH SPECIAL POLYMERS:** Our polymer package reduces oil separation and stays in application longer while resisting water washout

**EXTREME PRESSURE PERFORMANCE:** An extreme pressure additive package helps moving components withstand heavy shock loads and prevents wear

### CONSTRUCTION RED GREASE

TEST METHOD	ASTM	TYPICAL PROPERTIES
NLGI	D-4950	GC-LB
Dropping Point, °F	D-2265	500
Penetration • Worked 60 strokes	D-217	270
Mineral Oil Viscosity • cSt. @40°C • cSt. @100°C	D-445 D-445	322 29.2
Viscosity Index	D-445	124
Color	Observed	Red
Soap, Type		Lithium Complex
Rust Prevention	D-1743	Pass
Oxidation Stability LB Loss/ 100 hrs.	D-942	2
Extreme Pressure • Timken, OK Load, LB • Four-Ball Weld Point, KGF • Four-Ball LWI	D-2509 D-2596 D-2596	80 400 40

Note: Values shown above are representative of current production and may vary within modest ranges.

Rev. 09/17

For additional qualifications, please contact your Performance Plus Products Sales Representative. The information on this Product Data Sheet is typical of current production. Specifications are subject to change.