



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

GL-5 GEAR OIL

PERFORMANCE PLUS™ GL-5 Gear Oils are premium quality multi-purpose gear oils formulated to minimize gear friction, reduce corrosion, and prevent the formation of sludge. It meets or exceeds API GL-5, Mack GO-G / GO-H performance standards for all vehicles and heavy-duty equipment differentials, final drives, manual transmissions and gearboxes, and is suitable for drain-and-fill or top-off limited-slip service. Also suitable for industrial gearboxes specifying US Steel 224.

PERFORMANCE PLUS PROPERTIES		
SAE Viscosity Grade	80W-90	85W-140
API Service	GL-5	GL-5
Kinematic Viscosity		
cSt @ 40°C	145.4	341.3
cSt @ 100°C	15.2	25.6
Viscosity Index	106	97
Brookfield Viscosity		
cSt @ -26°C	105000	-
cSt @ -12°C	-	60000
Color	L 3.5	L 4.5
Specific Gravity @ 15°C (60°F)	0.885	0.896
Flash Point, °C	214	218
Pour Point, °C	-30	-12

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 03/18