



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

PERFORMANCE PLUS FULL SYNTHETIC 50W TRANSMISSION FLUID

PERFORMANCE PLUS® Full Synthetic Heavy Duty SAE 50 Transmission Fluid is designed for use in manual transmissions where non-EP gear oils are specified. This products meets or exceeds following requirements: Eaton Roadranger PS-164 Rev. 7, Mack Truck: TO-A Plus; International Truck: TMS-6816; Meritor: O-81; ZF Driveline: ZF FreedomLine (ZF-AS Tronic); Volvo: 97305; and it is recommended for light to severe-duty on and off-highway equipment operating year-round.

PERFORMANCE PLUS HEAVY DUTY 50W FULL SYN TRANSMISSION FLUID

TEST METHOD	ASTM	TYPICAL PROPERTIES
API Gravity	D-4052	35.1
ASTM Color	D-1500	1.7
Specific Gravity 15°C (60°F)	D-4052	.846
Kinematic Viscosity		
cSt @ 40°C	D-445	103.50
cSt @ 100°C	D-445	17.40
Viscosity Index	D-2270	185
Flash Point, COC °C (°F)	D-92	235°C (455°F)
Brookfield Viscosity cP @ -40 °C	D-2983	130,000

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 11/22