



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

PERFORMANCE PLUS® FULL SYNTHETIC HEAVY DUTY TRANSMISSION FLUID

PERFORMANCE PLUS® Full Synthetic Heavy Duty Transmission Fluid is a fully synthetic fluid formulated to meet the demanding requirements of the latest heavy duty automatic transmissions and is recommended for use in applications where comparable Allison TES-295 & TES-389 performance capability is specified. Providing outstanding power transfer and gear shifting performance, it is made to: protect against thermal breakdown at high and sub-zero temperatures, offer excellent shear stability, and provide outstanding performance in severe operating conditions. Performance Plus Full Synthetic Heavy Duty Transmission Fluid is designed to protect transmissions against corrosion, oxidation and deposits delivering smooth shifting and prevent wear. Suitable for use in applications calling for MAN 339 Type V2; MAN 339 Type Z1, Z2, V1; Voith 55.6335 (G607), G1363; Volvo 97340, 97341, 97342; ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 14B, 16L, 17C.

TES-295® is a registered trademark of Allison Transmission Corporation.

PERFORMANCE PLUS PROPERTIES	
Meets Allison	TES-295, TES-389
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	34.8 7.3
Viscosity Index	184
Brookfield Viscosity cP @ -40°C	8,000
Specific Gravity @ 15°C	0.848
Flash Point, °C	220
Pour Point, °C	-51
Color	Red

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 4/18