



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

FULL SYNTHETIC HEAVY DUTY TRANSMISSION FLUID

PERFORMANCE PLUS™ Full Synthetic Heavy Duty Transmission Fluid is a fully synthetic fluid formulated to meet the demanding requirements of the latest heavy duty automatic transmissions and is recommended for use in applications where comparable Allison TES-295 & TES-389 performance capability is specified. It is also suitable for use in applications calling for API GL-1 and MT-1; Navistar/International TMS 6816; Mack TO-A Plus; Volvo I-Shift; Meritor O-81; and ZF Freedomline.

TES-295® and TES-389® are registered trademarks of Allison Transmission Corporation.

PERFORMANCE PLUS FULL SYNTHETIC HEAVY DUTY TRANSMISSION FLUID

TEST METHOD	ASTM	TYPICAL PROPERTIES
Allison TES-295	--	Meets
Allison TES-389	--	Meets
Specific Gravity 15.6 °C (60°F)	D-4052	.848
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	D-445 D-445	34.8 7.3
Viscosity Index	D-2270	184
Brookfield Viscosity cP @ -40°C	D-2983	8,000
Pour Point, °C	D-5950	-51 °C (-60 °F)
Color	D-1500	1.5 w/ASTM Test or Red w/Observed
Gravity	D-287	35.42

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 11/22