



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

dexos1™ FULL SYNTHETIC PASSENGER CAR MOTOR OIL

PERFORMANCE PLUS™ dexos1™ Full Synthetic Passenger Car Motor Oil are approved and licensed to meet GM's stringent requirements for dexos1™ passenger car engine oils.

They are specially formulated with a combination of Group III base oils plus state-of-the art performance additives. And they are engineered to meet or exceed the demands of all engines that specify GM dexos™ approved 0W-20, 5W-20, and 5W-30 engine oils. They also meet or exceed the requirements of Resource Conserving engine oils for API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL and previous ILSAC categories.

PERFORMANCE PLUS PROPERTIES

SAE Viscosity Grade	0W-20	5W-20	5W-30
GM Approved	dexos1™	dexos1™	dexos1™
API Service	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5
Kinematic Viscosity cSt @ 100°C cSt @ 40°C	8.4 44.8	8.5 48.3	11.0 63.9
Viscosity Index	167	154	165
CCS Viscosity cP @ -35°C cP @ -30°C	5600 -	- 4800	- 4900
MRV Viscosity cP @ -40°C cP @ -35°C	< 40000 -	- < 40000	- < 40000
Evaporative Loss, NOACK, wt%	< 13	< 13	< 13
Specific Gravity @ 15°C (60°F)	0.846	0.850	0.849
Flash Point, °C	230	230	232
Pour Point, °C	-42	-39	-36
Color (ASTM)	3.0	3.0	3.0
Sulfated Ash, wt%	< 1.0	< 1.0	< 1.0

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17