



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

FULL SYNTHETIC PASSENGER CAR MOTOR OIL

PERFORMANCE PLUS™ Full Synthetic Passenger Car Motor Oils are specially formulated with high-quality Group III base oil plus state-of-the-art performance additives. They are engineered to meet or exceed the demands of turbocharged, high powered, high-efficiency, gasoline and propane engines in the latest model passenger cars and light duty trucks.

PERFORMANCE PLUS PROPERTIES					
SAE Viscosity Grade	0W-20	5W-20	5W-30	10W-30	5W-40
API Service	SN	SN	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5	GF-5	-
Kinematic Viscosity					
cSt @ 40°C	46.3	48.7	62.7	67.3	90.5
cSt @ 100°C	8.7	8.6	10.8	10.5	14.7
Viscosity Index	169	157	164	144	170
CCS Viscosity					
cP @ -35°C	5600	-	-	-	-
cP @ -30°C	-	4600	5000	-	6000
cP @ -25°C	-	-	-	5200	-
Evaporative Loss, NOACK, wt%	< 15	< 15	< 15	< 15	< 15
Specific Gravity 15.6°C (60°F)	0.846	0.850	0.850	0.856	0.852
Flash Point, °C	210	208	204	204	208
Pour Point, °C	-51	-48	-48	-42	-45
Color (ASTM)	3.0	3.0	3.0	3.0	3.0
Sulfated Ash, wt%	0.92	0.92	0.92	0.92	0.92

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17