



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

AUTOMATIC TRANSMISSION FLUID

PERFORMANCE PLUS™ Automatic Transmission Fluid is formulated to reduce wear, protect against corrosion, and last longer in vehicles with automatic and power-shift transmissions. It is recommended for domestic and imported transmissions that specify DEXRON® III, DEXRON® IIE, DEXRON®, MERCON®, Ford ESP-M2C138-CJ, Ford ESP-M2C166-H or Type A Suffix A, Allison C-3/C-4, or Caterpillar TO-2 fluids.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

PERFORMANCE PLUS PROPERTIES

	ATF
Specific Gravity 15.6°C (60°F)	0.862
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	32.9 7.0
Viscosity Index	180
Brookfield Viscosity cP @ -40°C	17700
Flash Point, °C	204
Pour Point, °C	-51
Color	Red

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17