



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

HEAVY DUTY DIESEL 10W-30 CJ-4/SN

PERFORMANCE PLUS™ Heavy Duty Diesel 10W-30 CJ-4/SN Engine Oil is specifically engineered to meet the latest requirements for EGR/EPF engines. Meets or exceeds API Service CJ-4/SN as well as older API categories CI-4 Plus, CI-4 and CH-4. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

PERFORMANCE PLUS PROPERTIES

SAE Viscosity Grade	10W-30
API Service	CJ-4/SN
Approved	
Mack Premium Plus	E0-0
Cummins CES	20081
Detroit Diesel PGOS	93K218
Volvo	VDS-4
Kinematic Viscosity	
cSt @ 40°C	81.8
cSt @ 100°C	12.2
Kinematic Viscosity	146
CCS Viscosity	
cP @ -25°C	6600
Flash Point, °C	222
Pour Point, °C	-33
Specific Gravity 15.6°C (60°F)	0.868
Color (ASTM)	4.5
TBN	9.5
Sulfated Ash, wt%	0.98

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

HEAVY DUTY DIESEL ENGINE OIL 15W-40 CJ-4/SN

PERFORMANCE PLUS™ Heavy Duty Diesel Engine Oil 15W-40 Engine Oil is specifically engineered to meet the latest requirements for EGR / EPF engines. Meets or exceeds API Service CJ-4 / SN as well as older API categories CI-4 Plus, and CI-4. 15W-40 meets or exceeds OEM specifications and is formally approved for Mack EO-O Premium Plus, Cummins CES 20081, Detroit Diesel PGOS 93K218 and Volvo VDS-4. Meets or exceeds Caterpillar ECF-1A, 2 and 3, MB 228.3, ACEA E7, and MTU Type II standards for performance and protection. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

PERFORMANCE PLUS PROPERTIES

SAE Viscosity Grade	15W-40
API Service	CJ-4/SN
Kinematic Viscosity cSt @ 40°C	118.5
cSt @ 100°C	15.7
Viscosity Index	141
CCS Viscosity cP @ -20°C	6300
Flash Point, °C	236
Pour Point, °C	-33
Specific Gravity 15.6°C (60°F)	0.871
Color (ASTM)	L 4.0
TBN	9.6
Sulfated Ash, wt%	0.98

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17