



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

HIGH MILEAGE PASSENGER CAR MOTOR OILS

PERFORMANCE PLUS™ High Mileage Motor Oil for passenger cars provides maximum protection for longer engine life in vehicles with over 75,000 miles. The formulation contains extra additives to help stop leaks and reduce oil consumption by conditioning seals and gaskets. Plus, it reduces sludge and damaging deposits.

Performance Plus High Mileage Motor Oils are specially formulated with Group II+ base oils plus state-of-the art performance additives and are engineered to exceed the demands of turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger cars and light duty trucks. SAE 5W-20, 5W-30, and 10W-30 grades are Resource Conserving motor oils that exceed API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL, and previous ILSAC categories.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

PERFORMANCE PLUS PROPERTIES

SAE VISCOSITY GRADES	5W-20	5W-30	10W-30
API Service	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5
Kinematic Viscosity			
cSt @ 40°C	49.7	63.2	69.5
cSt @ 100°C	8.6	10.6	10.6
Viscosity Index	150	155	140
CCS Viscosity			
cSt @ -30°C	6100	6300	-
cSt @ -25°C	-	-	6300
Evaporative Loss, NOACK, wt%	< 15	< 15	< 15
Specific Gravity @ 15°C (60°F)	0.861	0.860	0.866
Flash Point, °C	218	224	234
Pour Point, °C	-39	-39	-36
Color (ASTM)	L 3.0	L 3.0	L 3.0

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 08/17