



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

HEAVY DUTY DIESEL ENGINE OIL SYNTHETIC BLEND 15W-40 CJ-4/SN

PERFORMANCE PLUS™ Heavy Duty Diesel Engine Oil Synthetic Blend 15W-40 Engine Oil is specifically engineered to meet the latest requirements for EGR / EPF engines. Meets or exceeds API Service CJ-4 / SN as well as older API categories CI-4 Plus, and CI-4. 15W-40 meets or exceeds Mack EO-O Premium Plus, Cummins CES 20081, Detroit Diesel PGOS 93K218 and Volvo VDS-4, Caterpillar ECF-1A, 2 and 3, MB 228.3, ACEA E-9 2012, Komatsu Tier 4i, and MTU Type II standards for performance and protection. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

This product is formulated with Group III base oils and Kleen Performance Products' hydro-treated,

PERFORMANCE PLUS PROPERTIES	
SAE Viscosity Grade	15W-40
API Service	CJ-4/SN
Kinematic Viscosity	
cSt @ 40°C	113.9
cSt @ 100°C	15.5
Viscosity Index	143
CCS Viscosity	
cP @ -20°C	5300
Flash Point, °C	236
Pour Point, °C	-36
Specific Gravity 15.6°C (60°F)	0.865
Color (ASTM)	L 4.0
TBN	9.6
Sulfated Ash, wt%	0.98

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17