



# Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

## HEAVY DUTY DIESEL HD-2

**PERFORMANCE PLUS™ HD-2 Heavy Duty Diesel Engine Oils** are engineered to reduce wear and tear on valve trains and rings while preventing sludge and carbon deposits. Recommended for naturally aspirated, turbocharged, or supercharged diesel, gasoline, and propane engines that require API CF-2, CF Service Categories (now obsolete), and power shift transmissions specifying Allison C-3 / C-4, and CAT TO-2.

The foundation of Performance Plus Oils are Kleen' Performance Products' hydro-treated, high VI, Group II+ base oils.

### PERFORMANCE PLUS PROPERTIES

SAE Viscosity Grade	30	40	50
API Service Also recommended for use in engines specifying:	CF-2, CF Detroit Diesel Two-Cycle (6V71 & 6V93)	CF-2, CF Detroit Diesel Two-Cycle (6V71 & 6V93)	CF-2, CF
Kinematic Viscosity cSt @ 40°C	94.6	123.5	185.1
cSt @ 100°C	12.1	14.4	18.4
Viscosity Index	121	117	112
Flash Point, °C	238	242	250
Pour Point, °C	-36	-27	-21
Specific Gravity @ 15°C (60°F)	0.874	0.880	0.888
Color (ASTM)	L 3.0	L 3.5	L 5.0
TBN	7.5	7.5	7.5
Sulfated Ash, wt%	0.86	0.86	0.86

**For additional qualifications, please contact your Performance Plus Products Sales Representative.**

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17