



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

HEAVY DUTY DIESEL 10W-30 FA-4

PERFORMANCE PLUS™ Heavy Duty Diesel 10W-30 FA-4 Engine Oil is specifically engineered to meet the latest requirements for EGR / EPF engines. 10W-30 FA-4 is a low viscosity product specifically designed to deliver additional fuel economy in newer model year engines. 10W-30 meets or exceeds API Service FA-4 with OEM approvals for Cummins CES 20087 and Detroit Diesel DFS 93K223. As always the customers should follow OEM recommendations.

The foundation of Performance Plus Oils are Kleen Performance Products' hydro-treated, high VI, Group II+ base oils.

PERFORMANCE PLUS PROPERTIES

SAE Viscosity Grade	10W-30
API Service	FA-4
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	66.3 10.2
Viscosity Index	140
CCS Viscosity cP @ -20°C	5,400
Flash Point, °C	237
Pour Point, °C	-39
Specific Gravity @ 60°F	0.86
Color (ASTM)	L 4.0
TBN	10.0
Sulfated Ash, wt%	1.0

For additional qualifications, please contact your Performance Plus Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 05/17