



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

WAY OIL

PERFORMANCE PLUS™ Way Oils are designed to increase the life of machine tools by providing proprietary anti-rust and friction additives for superior protection.

They are approved for use in General Motors, Ford, and Chrysler and are ideal for use in planers, grinders, horizontal boring machines, shapers, jig borers and milling machines.

The foundation of Performance Plus Oils are hydro-treated, high VI base oils.

PERFORMANCE PLUS PROPERTIES		
ISO Viscosity Grade	68	220
Kinematic Viscosity cSt @ 40°C	69.6	230.1
cSt @ 100°C	9.4	20.1
Viscosity Index	113	100
Specific Gravity @ 15°C (60°F)	0.868	0.883
Color	L 2.5	L 3.5
Flash Point, °C	236	242
Pour Point, °C	-27	-12
Demulsibility D1401	Pass	Pass
Demulsibility D2711 Free water, mL	-	83.0
Water in oil, %	-	Trace
Emulsion, mL	-	0
Rust Characteristics D 665B	Pass	Pass
TAN	0.28	0.28
Copper Corrosion	1B	1B
Precipitation Number	< 0.05	< 0.05
Timken OK Load	65	60

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 07/18

For additional qualifications, please contact your Performance Plus Products Sales Representative.