

QCMD 4-690

Untreated compressed air is dirty. In order to keep these contaminants from wreaking havoc on compressed air piping and tools, it is important to incorporate high quality compressed air treatment equipment. That's why Quincy offers the ultra reliable, long-lasting QCMD desiccant dryer. With integrated ceramic desiccant technology, the QCMD comes with the longest-lasting desiccant around.



- 1 7-Year Desiccant Life (12-690)
- 2 Advanced Controllers
- 3 Dual Filtration Included
- 4 Energy Saving Dew Point Sensors
- 5 Compact Package Design
- 6 Horizontal Install Option (12-690)

QCMD 4-690 CFM Heatless Desiccant Air Dryers

The QCMD Series Is Best For:

- ✓ Professional and industrial applications that demand longevity and durability
- ✓ Applications that require ultra dry compressed air (-40°F dew point)
- ✓ Applications that utilize heavy compressed air loads and usage
- ✓ Applications that have little head-room and require horizontal installations

QCMD MODELS AND SPECIFICATIONS

Model	Inlet/Outlet Pipe Size (NPT)	Voltage/Phase/Hz	Package kW	Inlet Flow Rate (SCFM)	Dimensions			Weight (lbs)
					Length (inches)	Width (inches)	Height (inches)	
QCMD 4	1/2"	Multiple	0.05	4	7.2	9.3	16.9	71
QCMD 7	1/2"	Multiple	0.05	7	7.2	9.3	20.7	82
QCMD 11	1/2"	Multiple	0.05	11	7.2	9.3	20.7	93
QCMD 12	3/8"	Multiple	0.05	12	15.6	14.3	37.4	71
QCMD 22	3/8"	Multiple	0.05	22	15.6	14.3	43.5	82
QCMD 32	3/8"	Multiple	0.05	32	15.6	14.3	49.6	93
QCMD 43	1/2"	Multiple	0.05	43	15.6	14.3	55.7	106
QCMD 53	1/2"	Multiple	0.05	53	15.6	14.3	62.8	119
QCMD 64	1/2"	Multiple	0.05	64	15.6	14.3	69.1	130
QCMD 90	1"	Multiple	0.05	89	24.4	15.5	47.4	247
QCMD 110	1"	Multiple	0.05	111	24.4	15.5	58.9	292
QCMD 135	1"	Multiple	0.05	133	24.4	15.5	58.9	320
QCMD 180	1"	Multiple	0.05	178	24.4	15.5	72.2	377
QCMD 220	1"	Multiple	0.05	222	24.4	22.2	58.9	495
QCMD 265	1 1/2"	Multiple	0.05	267	24.4	22.2	58.9	539
QCMD 355	1 1/2"	Multiple	0.05	356	24.4	22.2	72.2	637
QCMD 400	1 1/2"	Multiple	0.05	400	24.4	28.9	58.9	766
QCMD 535	2"	Multiple	0.05	534	24.4	28.9	72.2	901
QCMD 690	2"	Multiple	0.05	689	24.4	36.6	72.2	1158

Reliability

- Long Service Intervals
- Simplified Valves/Controls
- Extremely Stable Dew Point

Quality

- 7-Year Desiccant Life
- Advanced Controllers
- Filtration Included

Efficiency

- Low Purse Design
- Dew Point Demand Options
- Low Pressure Loss



WARRANTY INFORMATION

2-YEARS

2-YEAR FACTORY WARRANTY



Twenty-four (24) months from date of shipment from the factory.

Parts - Ninety (90) days from date of Distributor sale or twelve (12) months from date of factory shipment, whichever occurs first.